



ZETTEX
STICK WITH US

TECHNICAL DATA SHEET

Fixing Tape

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Zettex Fixing Tape is an extremely strong UV-resistant, double-sided tape for rapidly fixing all types of sheet material.

Application

Zettex Fixing Tape can be used indoors and outdoors and has high initial adhesion. Zettex Fixing Tape is used mainly as a temporary fixing product for façade and wall coverings. With a thickness of 3mm, this tape produces the required adhesive layer thickness.

Directions for use

Apply the fixing tape to a dry, grease-free surface and press firmly.

Properties	Specifications
Density	kg/mtr ³ : 29
Longitudinal tensile strength	K.p.a.: 320
Transverse	K.p.a.: 205
Elongation	130%
Puncture resistance 10%	K.p.a. 13
Puncture resistance 25%	K.p.a. 32
Puncture resistance 50%	K.p.a. 95
Temperature resistance	-/-80C° - +/- 100C°
Processing temperature	+/+5C° - +/- 50C°
Shore hardness	15/48
Delivery forms	Roll: 25 meters - Dimensions: 3x12 mm - Box contents: 25 rolls