



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Spraybond X10 Canister

Zettex Europe B.V.

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31 (0)888-93 88 39

info@zettex.com

www.zettex.com

Product description

Zettex Spraybond X10 is a fast-drying universal spray adhesive for use on most construction and industry materials.

Material

SBR Rubber

Product properties

- Fast drying
- Extremely powerful
- High solids content
- For universal use
- Ready to use
- DCM free

Areas of application

For gluing all types of carpet, cork, linoleum, insulation material and rubber.

Applications

Remove any moisture and grease from the surface being glued. Gently spray the contact adhesive onto both surfaces being glued. The ideal distance between the surface and the spray gun is 30 cm. Try to apply the glue in a single layer. Bring the surfaces together after 2-4 minutes and press or roller firmly. Wait at least twice as long to glue the surfaces together if the layers applied have overlapped. Check thoroughly to see whether there is sufficient contact between the glue layers if the surface is porous. Apply an extra layer, if necessary.

Packaging

- Aerosol 500 ml
- Pressurized cylinder 17 L

Colour

Transparent

Safety recommendations

Make sure you have read our MSDS (Material Safety Data Sheet) before using this product.

Properties	Specifications
Processing temperature	+5 to +40 °C
Temperature resistance	-40 to + 55°C
Consumption	70-80 gram/m2
Open time	2-3 min
Maximum yield	120 m2
Solids	32 %
Color	Amber

