



**ZETTEX**  
STICK WITH US

## TECHNICAL DATA SHEET Spraybond X45 Canister

Zetex Europe B.V.  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31 (0)888-93 88 39  
[info@zettex.com](mailto:info@zettex.com)  
[www.zettex.com](http://www.zettex.com)

### Product description

Zetex Spraybond X45 is a very high quality heatresistant contact adhesive for gluing all sorts of products on any surface.

### Material

SBR Rubber

### Product properties

- Very powerful
- Heat resistant
- Extremely powerful
- Fast drying
- For universal use
- Ready to use
- DCM Free

### Areas of application

For gluing all types of surfaces. Due to the high solids and rubber content, this adhesive is extremely strong and safe to use. Zetex Spraybond X45 is also suitable for gluing surfaces sensitive to plasticizers such as PVC. The amount of plasticizer in the PVC must not exceed 16%. Testing is recommended before use.

### Applications

Remove any moisture and grease from the surface being glued. Gently spray the contact adhesive onto both surfaces being glued. The ideal distance between the surface and the spray gun is 30 cm. Try to apply the glue in a single layer. Bring the surfaces together after 2-4 minutes and press or roller firmly. Wait at least twice as long to glue the surfaces together if the layers applied have overlapped. Check thoroughly to see whether there is sufficient contact between the glue layers if the surface is porous. Apply an extra layer, if necessary.

### Packaging

Pressurized cylinder 17 L

### Colour

Amber

### Safety recommendations

Make sure you have read our MSDS (Material Safety Data Sheet) before using this product.

Properties	Specifications
Processing temperature	+5 to +40 degrees
Temperature resistance	-40 to +140°C
Consumption	60-70 gramm/m2
Open time	4-6 min
Maximum yield	200 m2

Solids	45 %
Color	Amber
Spray pattern	WEB
VOC	544 g/l