



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Easycontact S10

Zettex Europe B.V.

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31 (0)888-93 88 39

info@zettex.com

www.zettex.com

Product description

Zettex Easycontact S10 is a quick-drying universal contact adhesive applied using a brush or roller. Zettex Easycontact S10 is suitable for most materials in construction and industry. This Easycontact S10 is applied with a brush or a roller. Besides the Easycontact S10 is DCM-free.

Material

SBR Rubber

Advantages

- Quick drying
- Extremely powerful
- High solid substance content
- For universal use
- Ready to use

Uses

For the adhesion of all kinds of carpeting, cork, linoleum, insulation material and rubber.

Application instructions

Dry the materials to be adhered and remove dust and grease. This can be done with Zettex Profireinger. Then carefully apply the contact adhesive using a brush or a roller. Preferably apply the adhesive rows without overlapping. After 2-4 minutes adhere both surfaces to each other and firmly press or roll. When there is overlapping the open time must at least be doubled. With very porous surfaces carefully check whether there is sufficient contact between both adhesive layers. Apply an extra layer if this is required.

Available form

Drum 1 kg, 2.5 kg, 5 kg, 10 kg, 25 kg, 50 kg, 200 kg and 1000 kg

Colour

Transparent or red

Safety recommendations

This technical information does not contain an MSDS (Material Safety Data Sheet). You must first fully read the MSDS before using this product.

| Properties | Specifications |
|------------------------|-------------------|
| Processing temperature | +5 to +40 degrees |
| Temperature resistance | -40°C to +55°C |