



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Spraybond X90 Canister

Zetex Europe B.V.

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31 (0)888-93 88 39

info@zettex.com

www.zettex.com

Product description

Zetex Spraybond X90 HT is a universal excellent hybride polymer based adhesive without isocyanate and plasticiser resistant for bonding all kind of roofing and flooring substrates. Spraybond X90 HT can be applied in a one-way stick and exhibits a high degree of strenght.

Material

Hybrid Polymers

Properties

- One component
- Solvent free
- Extremely powerful
- Fast drying
- Plasticiser resistant
- For universal use
- Ready to use
- One side applying
- Nonflammable
- Economical in use
- Permanent flexible bond
- Low foaming
- High temperature resistance
- No plasticizer migration
- Unilaterally applied

Areas of application

For the fast and effective adhesion of all types of roof and floor surfaces, such as; PVC, EPDM, TPO, Bitume, Linoleum, Marmoleum and PU based surfaces.

Applications

Remove any moisture and grease from the surface being glued. Gently spray the contact adhesive on to surface being glued. The ideal distance between the surface and the spray gun is 30 cm. Try to apply the glue in a single layer. Bring the surfaces together after 2-4 minutes and press or roller firmly. Check thoroughly to see whether there is sufficient contact between the glue layers if the surface is porous. Apply an extra layer, if necessary.

Packaging

Pressurised cylinder 23kg

Colour

Brown, others on request

Safety recommendations

Make sure you have read our MSDS (Material Safety Data Sheet) before using this product.

Properties

Specifications

Processing temperature	- 5 till + 40 degrees
Temperature resistance	- 40 till + 150 degrees
Usage	120 gram/m2
Open time	15 min
Maximum Coverage	175 m2
Solids Content	50 %
Colour	Brown
VOC	407 g/l
Spray Pattern	WEB