

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**Trade name: **Zettex Spraybond X70 Primer****1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.Application of the substance / the mixture *Adhesives***1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**Zettex Europe BV  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31(0)888-938839  
info@zettex.nl  
www.zettex.nl**1.4 Emergency telephone number:** NVIC-Nederland. Tel: +31-30-2748888 (only medical personnel)**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

GHS02



GHS07



GHS09

**Signal word** *Danger***Hazard-determining components of labelling:**

cyclohexane

Naphtha (petroleum), hydrotreated light

ethyl acetate

**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from open flames. - No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 2)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

**Trade name: Zettex Spraybond X70 Primer**

(Contd. of page 1)

- P280 Wear protective gloves / eye protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER/doctor if you feel unwell.  
 P402+P404 Store in a dry place. Store in a closed container.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Contains zinc bis(dibutyldithiocarbamate). May produce an allergic reaction.  
 Restricted to professional users.

**2.3 Other hazards**

- **Results of PBT and vPvB assessment** Not applicable.
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

|   |  |         |
|---|--|---------|
| CAS: 110-82-7<br>EINECS: 203-806-2<br>Reg.nr.: 01-2119463273-41   | cyclohexane<br>⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410;<br>⚠ Skin Irrit. 2, H315; STOT SE 3, H336                | 40-<60% |
| CAS: 64742-49-0<br>EINECS: 265-151-9<br>Reg.nr.: 01-2119475133-43 | Naphtha (petroleum), hydrotreated light<br>⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315;<br>STOT SE 3, H336           | 10-<20% |
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46   | ethyl acetate<br>⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336   | 5-<10%  |
| CAS: 136-23-2<br>EINECS: 205-232-8<br>Reg.nr.: 01-2119535161-51   | zinc bis(dibutyldithiocarbamate)<br>⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | <0.5%   |

**Additional information:**

"Naphtha" classified and marked in accordance with EU Directives RL 67/548/EWG, Note P.[contents benzene (CAS: 71-43-2) <0,1% by weight]

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**
**General information:**

Personal protection for the First Aider.

Remove contaminated clothing. If symptoms persist or in cases of doubt seek medical advice.

**After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

If the casualty is not breathing: Perform mouth-to-mouth or mouth-to-nose resuscitation, notify emergency physician immediately

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:**

Rinse mouth with water.

If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

**SECTION 5: Firefighting measures**
**5.1 Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

**Trade name: Zettex Spraybond X70 Primer**

(Contd. of page 2)

· **5.2 Special hazards arising from the substance or mixture**

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Carbon monoxide (CO)

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

\* **SECTION 6: Accidental release measures**

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

\* **SECTION 7: Handling and storage**

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

As of July 2003, organizations in the EU must follow the directives to protect employees from explosion risk in areas with an explosive atmosphere.

There are two ATEX directives (one for the manufacturer and one for the user of the equipment):

- the ATEX 95 equipment directive 94/9/EC, Equipment and protective systems intended for use in potentially explosive atmospheres;
- the ATEX 137 workplace directive 99/92/EC, Minimum requirements for improving the safety and health protection of workers potentially at risk from explosive atmospheres.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **7.3 Specific end use(s)** No further relevant information available.

\* **SECTION 8: Exposure controls/personal protection**

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**110-82-7 cyclohexane**

WEL Short-term value: 1050 mg/m<sup>3</sup>, 300 ppm

Long-term value: 350 mg/m<sup>3</sup>, 100 ppm

**141-78-6 ethyl acetate**

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm

Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

(Contd. on page 4)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

Trade name: **Zettex Spraybond X70 Primer**

(Contd. of page 3)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Wear high-quality protective equipment during operations such as grinding, drilling and/or sawing

Dust mask FFP3 (Filtering Facepiece Partikel) (EN 149: 2001)

Gloves (grinding) (EN388 (4.1.3.1))

Safety glasses (EN166-168, 170)

Hearing protection (EN352-2)

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Store protective clothing separately.

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not carry product impregnated cleaning cloths in trouser pockets.

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Oxygen content of the inhalation air must be sufficient i.e. > 17%

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AXP3(EN371)

· **Protection of hands:**



Protective gloves

Nitrile rubber gloves(EN374, EN388:4101).

Permeation EN374-3: 2003 (minutes)> 480 minutes

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

While wearing protective gloves cotton single-use undergloves are recommendable. However, these undergloves must be discarded after each use to avoid potential exposure to absorbed product.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Nitril rubber, NBR

· **For contact of maximum 15 minutes, gloves made of the following materials are suitable:** Nitrile rubber, NBR

· **Eye protection:**



Tightly sealed goggles

Safety glasses(EN166)

· **Body protection:** Protective work clothing(EN 340, 463, 468, 943-1, 943-2)

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Colour: Black

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

Trade name: **Zettex Spraybond X70 Primer**

(Contd. of page 4)

|  |   |
|--|---|
| · <b>pH-value:</b>                                     | Not applicable.   |
| · <b>Change in condition</b>                           |   |
| <b>Melting point/freezing point:</b>                   | Undetermined.   |
| <b>Initial boiling point and boiling range:</b>        | 60 °C   |
| · <b>Flash point:</b>                                  | -20 °C  |
| · <b>Ignition temperature:</b>                         | Not determined.   |
| · <b>Decomposition temperature:</b>                    | Not determined.   |
| · <b>Auto-ignition temperature:</b>                    | Product is not selfigniting.  |
| · <b>Explosive properties:</b>                         | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>                             |   |
| <b>Lower:</b>  | 1.3 Vol %   |
| <b>Upper:</b>  | 8.3 Vol %   |
| · <b>Vapour pressure at 20 °C:</b>                     | 175 hPa   |
| · <b>Density at 20 °C:</b>                             | 0.84 g/cm <sup>3</sup>  |
| · <b>Vapour density</b>                                | Not determined.   |
| · <b>Evaporation rate</b>                              | Not determined.   |
| · <b>Solubility in / Miscibility with water(20°C):</b> | Not miscible or difficult to mix.   |
| · <b>Partition coefficient: n-octanol/water:</b>       | Not determined.   |
| · <b>Viscosity:</b>                                    |   |
| <b>Dynamic at 20 °C:</b>                               | 900 mPas  |
| <b>Kinematic at 40 °C:</b>                             | 635 mm <sup>2</sup> /s  |
| <b>ISO DIN Cup 6 mm (23°C)</b>                         | 58 sec  |
| · <b>Solvent content:</b>                              |   |
| <b>Organic solvents:</b>                               | 63.4 %  |
| <b>VOC (EG)</b>  | 532.3 g/l   |
| · <b>VOC% (EC)</b>                                     | 63.37 %   |
| · <b>Solids content:</b>                               | 36.6 %  |
| · <b>9.2 Other information</b>                         | No further relevant information available.  |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Oxidizing agents
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**  
The product has not been tested. The statements underneath have been derived from the properties of the individual components.
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

##### 110-82-7 cyclohexane

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | >5,000 mg/kg (Rat)    |
| Dermal | LD50 | >2,000 mg/kg (Rabbit) |

##### 141-78-6 ethyl acetate

|      |      |                      |
|------|------|----------------------|
| Oral | LD50 | 5,620 mg/kg (Rabbit) |
|------|------|----------------------|

(Contd. on page 6)

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

Trade name: **Zettex Spraybond X70 Primer**

(Contd. of page 5)

|  |          |                    |
|--|----------|--------------------|
| Inhalative                                       | LC50, 4h | 1,600 mg/l (Rat)   |
| <b>136-23-2 zinc bis(dibutyldithiocarbamate)</b> |          |                    |
| Oral   | LD50     | >2,000 mg/kg (Rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

#### SECTION 12: Ecological information

##### 12.1 Toxicity

###### Aquatic toxicity:

##### 110-82-7 cyclohexane

LC50, 96h 4.53 mg/l (Fathered minnow, *Pimephales promelas*)EC50, 48h 0.9 mg/l (*Daphnia magna*)EC50, 72h 3.4 mg/l (*Algae*)

##### 141-78-6 ethyl acetate

LC50, 96h >230 mg/l (*Fish*)EC50, 24h >164 mg/l (*Daphnia magna*)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Other information:**  
Ecotoxicological data have not been determined specifically for this product. Information given is based on knowledge of the components and the ecotoxicology of similar products.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

#### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue** Please contact your waste disposer for the exact waste code.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9






Revision: 30.03.2020

Trade name: Zettex Spraybond X70 Primer

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

|   |   |
|---|---|
| · <b>14.1 UN-Number</b><br>· <b>ADR, IMDG, IATA</b>   | UN1133  |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR</b><br>· <b>IMDG</b><br>· <b>IATA</b>   | 1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS<br>ADHESIVES (CYCLOHEXANE, Naphtha (petroleum), hydrotreated<br>light), MARINE POLLUTANT<br>ADHESIVES |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR</b>  |   |
|       |   |
| · <b>Class</b><br>· <b>Label</b>  | 3 (F1) Flammable liquids.<br>3  |
| · <b>IMDG</b>   |   |
|   |   |
| · <b>Class</b><br>· <b>Label</b>  | 3 Flammable liquids.<br>3   |
| · <b>IATA</b>   |   |
|    |   |
| · <b>Class</b><br>· <b>Label</b>  | 3 Flammable liquids.<br>3   |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>   | II  |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b><br>· <b>Special marking (ADR):</b>   | Product contains environmentally hazardous substances: cyclohexane<br>Yes<br>Symbol (fish and tree)<br>Symbol (fish and tree)                   |
| · <b>14.6 Special precautions for user</b><br>· <b>Hazard identification number (Kemler code):</b><br>· <b>EMS Number:</b><br>· <b>Stowage Category</b>                 | Warning: Flammable liquids.<br>33<br>F-E, S-D<br>B  |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>  | Not applicable.   |
| · <b>Transport/Additional information:</b>  |   |
| · <b>ADR</b><br>· <b>Limited quantities (LQ)</b><br>· <b>Excepted quantities (EQ)</b>   | 5L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml                           |

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

Trade name: **Zettex Spraybond X70 Primer**

(Contd. of page 7)

|                                   |   |
|-----------------------------------|---|
| · <b>Transport category</b>       | 2   |
| · <b>Tunnel restriction code</b>  | D/E   |
| · <b>Remarks:</b>                 | The product is, based on the viscosity, classified in accordance with ADR, Part 2, Chapter 2.2, Paragraph 2.2.3.1.4 |
| <hr/>                             |   |
| · <b>IMDG</b>                     |   |
| · <b>Limited quantities (LQ)</b>  | 5L  |
| · <b>Excepted quantities (EQ)</b> | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml    |
| · <b>Remarks:</b>                 | The product is, based on the viscosity, classified in accordance with IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.   |
| · <b>UN "Model Regulation":</b>   | UN 1133 ADHESIVES, 3, II, ENVIRONMENTALLY HAZARDOUS   |

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E1 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57

#### · **National regulations:**

| Class | Share in % |
|-------|------------|
| NK    | 60-<80     |

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

#### · **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 30.03.2020

Version: 9

Revision: 30.03.2020

**Trade name: Zettex Spraybond X70 Primer**

(Contd. of page 8)

Skin Sens. 1: Skin sensitisation – Category 1  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

**Sources**

Classification corresponds to the current lists of the EEC, is supplemented with data from publications and data from the company.

\* **Data compared to the previous version altered.**

**DISCLAIMER:**

Information and details given in this document, particularly any recommendations for application and use of our products are based on careful laboratory tests and prevailing practical experience and are believed to be correct at time of publication. The information is not binding, which is also generally true for our practical customer service, given verbally, in writing and by tests. Due to (possibly varying) conditions of transport, storage, process, substrate use or product application (which are beyond our knowledge and control), we strongly recommend to carry out sufficient tests in order to ensure that our products are suitable for the intended processes and applications.

Further, it is the user's obligation to utilize this material with due care, in accordance with the information in the Material Safety Datasheet (and with the information given in any other way by Zettex) and in full compliance with health, safety and environmental regulations. Whilst proper care has been taken in the preparation of this document, no liability for damage or injury resulting from its use is accepted, other than the limited liability which may arise towards a contractual party on the basis of Zettex conditions of sale (a copy of these conditions is available on request).

Zettex acceptance of any orders for this product is expressly conditional upon purchaser's assent to these conditions of sale. No information contained in this document (nor any information given verbally, in writing and by tests) is to be construed as permission, recommendation or inducement by Zettex or its officers, employees or affiliates, to use any product or process so as to infringe upon or conflict with any patent. Zettex does not attest or guarantee that the use of its products or processes will not infringe upon any patent; user is responsible for verifying its freedom to operate in any jurisdiction.