



**ZETTEX**  
STICK WITH US

## TECHNICAL DATA SHEET Spraybond X50 Canister

**Zettex Europe B.V.**  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31 (0)888-93 88 39  
[info@zettex.com](mailto:info@zettex.com)  
[www.zettex.com](http://www.zettex.com)

### Product description

Zettex Spraybond X50 is a very high-quality contact adhesive without solvents or plasticisers for gluing all types of EPS, XPS and PU.

### Material

SBR Rubber

### Product properties

- Very fast
- Solvent free
- Extremely powerful
- Fast drying
- For universal use
- Ready to use
- DCM Free

### Areas of application

For the fast and effective adhesion of all solvent-sensitive surfaces such as EPS, XPS and PU. The adhesive is completely non-corrosive. If using on a roof, it is important to check whether the adhesive is sufficiently heat resistant for the intended purpose.

### Applications

Remove any moisture and grease from the surface being glued. Gently spray the contact adhesive onto both surfaces being glued. The ideal distance between the surface and the spray gun is 30 cm. Try to apply the glue in a single layer. Bring the surfaces together after 4-6 minutes and press or roller firmly. Wait at least twice as long to glue the surfaces together if the layers applied have overlapped. Check thoroughly to see whether there is sufficient contact between the glue layers if the surface is porous. Apply an extra layer, if necessary.

### Packaging

Pressurized cylinder 17 L

### Colour

Amber

### Safety recommendations

Make sure you have read our MSDS (Material Safety Data Sheet) before using this product.

Properties	Specifications
Processing temperature	+5 to +40 degrees
Temperature resistance	-40 to + 80°C
Consumption	70-80 Gramm/m2
Open time	3-4 min
Maximum yield	150 m2

Solids	30 %
Color	Amber
Spray pattern	WEB
VOC	544 g/l