



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Rooftex

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Zettex Rooftex is a unique repair, mounting and caulking adhesive formulated on the basis of rubber with a glass fibre reinforcement. Can be applied to wet substrates. Can be used over a wide temperature range: (from -12 °C to +50°C.)

Material

Fiber-reinforced bitumen

Advantages

- For reparation of cracks, tears and blistering on bituminous roofs and gutters.
- Finishing mastic for sealing seams between roofing sheets around chimneys, drains, domes, elevations and air ducts.
- Adhesion of shingles and insulation (insulation must be solvent-compatible).
- Can also be used as a cold adhesive for installing corrugated roofing sheets, skylights and dome lights.
- Excellent bonding of steel, zinc, lead, copper, tin, wood, stone, concrete, asphalt, pvc and polyester.
- Can be applied on wet surfaces

Instructions

Apply Zettex Rooftex to surfaces that are free of dirt and grease. Clean tools with Zettex Proficleaner.

Packaging

Cartridge 310 ml.

Safety recommendations

Make sure you have read our MSDS carefully before using this product.

Storage

Can be stored for a period of up to 12 months, if stored in a dray location and in well-sealed packaging. Keep free from frost.

Properties	Specifications
UV stability	Good
Water resistance	Good
Processing temperature	-12 °C to +50°C
Base	Bitumen, rubber, polymers, resin and fibre fortification
Physical state	Viscous paste
Colour	Black
Flash point cc (astm d93)	>55 °C (Pensky Martens)
Viscosity	>60 sec (150 Cup 6 mm, 23 °C)
Density	Ca 1,29 kg/L at 20 °C
Fluidity	Nil

Solid matter	Ca 88 %
--------------	---------