



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Silgliss Lubricant

Zettex Europe B.V.
Plaza 20, 4782 SK Moerdijk
The Netherlands
+31 (0)888-93 88 39
info@zettex.com
www.zettex.com

Product description

Silgliss Glijmiddel is a silicone-free lubricating jelly and lubricant. This product reduces friction, makes antistatic and leaves no residues. Silgliss Glijmiddel also does not stick or attach so deposits of dust and dirt are prevented. This lubricant can be used on surfaces that are to be coated, adhered or printed.

Material

Synthetic wax

Advantages

- Also suitable as a lubricant for wheel bearings, hinges, sliding doors, etc.
- Extends the life of sanding material.
- Reduces friction.
- Does not stick, attracts no dirt.
- Parts remain glueable and can be painted over.
- Spray can without propellant, for use in all positions.

Application Instructions

Silgliss is suitable as a lubricant for spindles and guide bars in wood processing machines. Also, for use on sanding and disk belts to prevent the clogging of the belt or disk. The working life of the sanding material is then extended by 20 to 50 %.

Dry the surface and remove dust and grease. Zettex Profireinger can be used for this. If you have applied too much Silgliss, this can be removed with the Zettex Witte or Bonte Tricot cloths. Hands can be cleaned with the Zettex Cleaning Wipes.

Available form

- Spray can 500 ml
- Drum 5 L

Colour

Transparent

Safety recommendations

See safety information sheet.

Properties	Specification
Type	Silicone-free dry lubricant
Colour	Colourless
Odour	Specific
Specific gravity	0.8 g/cm ³
Solubility	Not water-soluble
Flammability	Flash point 40 °C
Temperature resistance	-+20 °C to 240 °C