## SAFETY DATA SHEET

www.zettex.com

Page 1/8

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: ZETTEX MULTI OIL 500 ML · Article number: 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC24 Lubricants, greases, release products · Process category PROC7 Industrial spraying PROC11 Non industrial spraying · Application of the substance / the mixture Lubricant · 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: Zettex Europe BV Plaza 20, 4782 SK Moerdijk The Netherlands +31(0)888-938839 info@zettex.nl www.zettex.nl • Further information obtainable from: Department Product Safety · 1.4 Emergency telephone number: +31(0)888-938839

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

## **SECTION 2: Hazards identification**

• 2.1 Classification of the substance or mixture

Classification acc	cording to Regu	lation (EC) N	o 1272/2008
--------------------	-----------------	---------------	-------------

GHS02 j	flame	
Aerosol 1	Н222-Н229	Extremely flammable aerosol. Pressurised container: May burst if heated.
GHS07 Skin Irrit. 2	H315	Causes skin irritation.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
	ng to Regulat	ion (EC) No 1272/2008 belled according to the CLP regulation.

(Contd. on page 2)

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

(Contd. of page 1)

Trade name: ZETTEX MULTI OIL 500 ML

· Hazard pictograms



· Signal word Danger

## · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

*H412 Harmful to aquatic life with long lasting effects.* 

#### · Precautionary statements

- *P101 If medical advice is needed, have product container or label at hand.*
- P102 Keep out of reach of children.
- *P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
- *P211* Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- *P501* Dispose of contents / container in accordance with regional regulations.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220 Press. Gas (Comp.), H280	12.5-<20%
EC number: 931-254-9 Reg.nr.: 01-2119484651-34-xxxx	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane Flam. Gas 1, H220 Press. Gas (Comp.), H280	10-<12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane � Flam. Gas 1, H220 Press. Gas (Comp.), H280	10-<12.5%
• Additional information: For the	wording of the listed hazard phrases refer to section 16.	

## SECTION 4: First aid measures

## • 4.1 Description of first aid measures

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

• *After skin contact: Immediately wash with water and soap and rinse thoroughly.* 

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

Trade name: ZETTEX MULTI OIL 500 ML

- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5:** Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

## **SECTION 6:** Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Keep away from ignition sources. Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13.

- *Ensure adequate ventilation.*  **6.4 Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- *Ensure good ventilation/exhaustion at the workplace. No special measures required.*
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

(Contd. of page 2)

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

#### Trade name: ZETTEX MULTI OIL 500 ML

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

## 106-97-8 butane

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the skin. Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

## · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• *Eye protection:* Not required.

# SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:
- Form:
- Colour:
- · Odour:
- Odour threshold:

Aerosol Colourless Solvent-like Not determined.

(Contd. on page 5)

GB

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

#### Trade name: ZETTEX MULTI OIL 500 ML

nH value.	(Contd. of pag
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	
Flash point:	<0 °C (<32 °F)
	Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>200 °C (>392 °F)
Decomposition temperature:	Not determined.
Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C (68 °F):	3,500 hPa (2,625.2 mm Hg)
Density at 20 °C (68 °F):	0.68 g/cm <sup>3</sup> (5.67 lbs/gal)
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	55.0 %
VÕC (EC)	
	371.3 g/l
· VOC-EU%	55.00 %
Solids content:	0.0 %
9.2 Other information	No further relevant information available.

## SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Page 6/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

(Contd. of page 5)

Trade name: ZETTEX MULTI OIL 500 ML

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity* Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- **SECTION 12: Ecological information**
- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- *Remark:* Harmful to fish
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- Harmful to aquatic organisms • 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

 • European waste catalogue

 20 01 13\*

 solvents

## 15 01 04 metallic packaging

· Uncleaned packaging:

· Recommendation: Non contaminated packagings may be recycled.

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	

### Page 7/8

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

## Trade name: ZETTEX MULTI OIL 500 ML

	(Contd. of pag
14.3 Transport hazard class(es)	
ADR	
<u>()</u>	
Class	2 5F Gases.
Label	2.1 2.1
IMDG, IATA	
A	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litr Category A. For AEROSOLS with a capacity above 1 litr
	Category A. For WASTE AEROSOLS with a capacity above 1 thr Category B. For WASTE AEROSOLS: Category C, Clear
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr
	Segregation as for class 9. Stow "separated from" class I
	except for division 1.4. For AEROSOLS with a capacity
	above 1 litre: Segregation as for the appropriate
	subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
147 Turnen out in bull according to the	
14.7 Transport in bulk according to Anne. Marpol and the IBC Code	<i>x II of</i> Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
	ν
IMDG Limited quantities (LO)	1L
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0
Excepten quantities (EQ)	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

(Contd. on page 8)

GB

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018

Version number 2

Revision: 06.11.2018

Trade name: ZETTEX MULTI OIL 500 ML

(Contd. of page 7)

GB

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: R&D legislation and regulatory advisor

· Contact:

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3