

according to 1907/2006/EC, Article 31

Page 1/12

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: Matt Black**
- **Article number: 970353**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture Paint**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Zettex Europe BV  
Plaza 20, 4782 SK Moerdijk  
The Netherlands  
+31(0)888-938839  
info@zettex.nl  
www.zettex.nl
- **1.4 Emergency telephone number: Zettex Europe BV 031 (0) 888 938 839 (Mon-Fri 09:00-17:00)**

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1            H222-H229    Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2            H319            Causes serious eye irritation.  
 STOT SE 3            H336            May cause drowsiness or dizziness.  
 Aquatic Chronic 3    H412            Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02    GHS07

- **Signal word Danger**
- **Hazard-determining components of labelling:**  
Acetone  
n-butyl acetate  
propan-2-ol
- **Hazard statements**  
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H319            Causes serious eye irritation.  
H336            May cause drowsiness or dizziness.  
H412            Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

GB

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 1)

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves / eye protection.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P403 Store in a well-ventilated place.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards****Results of PBT and vPvB assessment**• **PBT:** Not applicable.• **vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures**• **Description:** Active substance with propellant**Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32 01-2119486136-34	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	1-<2.5%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas (Comp.), H280	1-<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	1-<2.5%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 2)

CAS: 31394-54-4 EINECS: 250-610-8	heptane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥0.25-<1%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	0.1-<1%
CAS: 78-83-1 EINECS: 201-148-0 Reg.nr.: 01-2119484609-23	butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	0.1-<1%

· **Additional information:**

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Water haze  
Fire-extinguishing powder  
Carbon dioxide  
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

See Section 13 for disposal information.

(Contd. of page 3)

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
  - Do not spray onto a naked flame or any incandescent material.
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
  - Store in a cool location.
  - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
  - Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
  - Store in cool, dry conditions in well sealed receptacles.
  - Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

#### Ingredients with limit values that require monitoring at the workplace:

##### 67-64-1 Acetone

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm
	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm

##### 106-97-8 butane (containing < 0.1 % butadiene (203-450-8))

WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

##### 74-98-6 propane

WEL	Long-term value: 1800 mg/m <sup>3</sup>
-----	---

##### 123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm

##### 100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm
	Long-term value: 441 mg/m <sup>3</sup> , 100 ppm
	Sk

##### 75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8))

WEL	Short-term value: 2400 mg/m <sup>3</sup>
	Long-term value: 1900 mg/m <sup>3</sup>

##### 67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 999 mg/m <sup>3</sup> , 400 ppm

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 4)

**141-78-6 ethyl acetate**

WEL	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm
	Long-term value: 734 mg/m <sup>3</sup> , 200 ppm

**78-83-1 butanol**

WEL	Short-term value: 231 mg/m <sup>3</sup> , 75 ppm
	Long-term value: 154 mg/m <sup>3</sup> , 50 ppm

**· DNELs****67-64-1 Acetone**

Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	2420 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	200 mg/m <sup>3</sup> (Consumer)
		1210 mg/m <sup>3</sup> (Worker)

**123-86-4 n-butyl acetate**

Inhalative	DNEL Acute-systemic	859.7 mg/m <sup>3</sup> (Consumer)
		960 mg/m <sup>3</sup> (Worker)
	DNEL Acute-local	859.7 mg/m <sup>3</sup> (Consumer)
		960 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	102.34 mg/m <sup>3</sup> (Consumer)
		480 mg/m <sup>3</sup> (Worker)
	DNEL Long term-local	102.34 mg/m <sup>3</sup> (Consumer)
		480 mg/m <sup>3</sup> (Worker)

**Reaction mass of ethylbenzene and xylene**

Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	14.8 mg/m <sup>3</sup> (Consumer)
		77 mg/m <sup>3</sup> (Worker)

**67-63-0 propan-2-ol**

Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer)
		888 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	89 mg/m <sup>3</sup> (Consumer)
		500 mg/m <sup>3</sup> (Worker)

**· PNECs****67-64-1 Acetone**

PNEC Marine water	1.06 mg/l (Undefined)
PNEC Freshwater sediment	30.4 mg/l(dry weight) (Undefined)
PNEC Soil	29.5 (Undefined)
PNEC Marine water sediment	3.04 mg/l(dry weight) (Undefined)

**123-86-4 n-butyl acetate**

PNEC Freshwater	0.18 mg/l (Undefined)
PNEC Marine water	0.015 mg/l (Undefined)
PNEC Freshwater sediment	0.981 mg/l(dry weight) (Undefined)
PNEC Intermittent release	0.36 (Undefined)

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 5)

PNEC Soil	0.0903 (Undefined)
PNEC Sewage Treatment Plant	35.6 mg/l (Undefined)
PNEC Marine water sediment	0.0981 mg/l(dry weight) (Undefined)
<b>Reaction mass of ethylbenzene and xylene</b>	
PNEC Freshwater	0.327 mg/l (Undefined)
PNEC Marine water	0.327 mg/l (Undefined)
PNEC Freshwater sediment	12.46 mg/l(dry weight) (Undefined)
PNEC Soil	2.31 (Undefined)
PNEC Sewage Treatment Plant	6.58 mg/l (Undefined)
PNEC Marine water sediment	12.46 mg/l(dry weight) (Undefined)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Filter A/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2P2

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm

· **Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 6)

**· Eye protection:**

Safety glasses



Tightly sealed goggles

**· Body protection:** Use protective suit. (EN-13034/6)**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

**Form:** Aerosol  
**Colour:** According to product specification

**· Odour:** Characteristic**· Odour threshold:** Not determined.**· pH-value:** Not determined.**· Change in condition****Melting point/freezing point:** Undetermined.**Initial boiling point and boiling range:** -44.5 °C**· Flash point:** -97 °C**· Flammability (solid, gas):** Not applicable.**· Auto-ignition temperature:** Product is not selfigniting.

**· Explosive properties:** Product is not explosive. However, formation of explosive air/  
vapour mixtures are possible.  
Not determined.

**· Explosion limits:****Lower:** 1 Vol %**Upper:** 13 Vol %

**· Vapour pressure at 20 °C:** 3200 hPa  
Not determined.

**· Density at 20 °C:** 0.75 g/cm<sup>3</sup>**· Relative density** Not determined.**· Vapour density** Not determined.**· Evaporation rate** Not applicable.**· Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**· Partition coefficient: n-octanol/water:** Not determined.**· Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.**· Solvent content:****Organic solvents:** 91.2 %**Solids content:** 8.3 %**· 9.2 Other information** No further relevant information available.

GB

(Contd. on page 8)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

Trade name: Matt Black

(Contd. of page 7)

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### 67-64-1 Acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	7800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)

##### 123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat)
Dermal	LD50	>14000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

#### Reaction mass of ethylbenzene and xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

##### 100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rbt)
Inhalative	LD50	>2000 mg/kg (rat)

##### 67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50/6h	25000 mg/m3 (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

Trade name: Matt Black

(Contd. of page 8)

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### 67-64-1 Acetone

EC50	8800 mg/l (Daphnia magna)
	8300 mg/l (Fish)

##### 123-86-4 n-butyl acetate

LC50/96h	18 mg/l (Fish)
EC50/48h	44 mg/l (Daphnia magna)

##### Reaction mass of ethylbenzene and xylene

NOEC	1.3 mg/l (Fish)
NOEC (7 day)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)

##### 100-41-4 ethylbenzene

LC50	>10 mg/l (Fish (96h))
EC50	>100 mg/l (Daphnia magna)

##### 67-63-0 propan-2-ol

LOEC (8 days)	1000 mg/l (algae)
LC50/96h	9640 mg/l (Pimephales promelas)
LC50 (24h)	9714 mg/l (Daphnia magna)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

#### · Ecotoxicological effects:

· **Remark:** Harmful to fish

#### · Additional ecological information:

##### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

##### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### · Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019



Version: 17

Revision: 20.02.2019

Trade name: Matt Black

(Contd. of page 9)

### SECTION 14: Transport information

<ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, ADN, IMDG, IATA</b></li> </ul>	UN1950
<ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR, ADN</b></li> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>	UN1950 AEROSOLS AEROSOLS AEROSOLS, flammable
<ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	2 5F Gases. 2.1
<ul style="list-style-type: none"> <li>· <b>ADN</b></li> <li>· <b>ADN/R Class:</b></li> </ul>	2 5F
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	2.1 2.1
<ul style="list-style-type: none"> <li>· <b>14.4 Packing group</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	Void
<ul style="list-style-type: none"> <li>· <b>14.5 Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	No
<ul style="list-style-type: none"> <li>· <b>14.6 Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Code</b></li>   <li>· <b>Segregation Code</b></li> </ul>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
<ul style="list-style-type: none"> <li>· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> </ul>	
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li>   <li>· <b>Transport category</b></li> </ul>	1L Code: E0 Not permitted as Excepted Quantity 2

(Contd. on page 11)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 10)

· <b>Tunnel restriction code</b>	D
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

#### · National regulations:

Class	Share in %
NK	75-<100

- VOC-CH 91.18 %
- VOC-EU 683.8 g/l
- Danish MAL Code 4-3
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: Research & Development

#### · Contact:

#### · Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

(Contd. on page 12)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date: 20.02.2019

Version: 17

Revision: 20.02.2019

**Trade name: Matt Black**

(Contd. of page 11)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Flam. Gas 1: Flammable gases – Category 1  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
 Asp. Tox. 1: Aspiration hazard – Category 1  
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **\* Data compared to the previous version altered. \***

GB