



ZETTEX

STICK WITH US

TECHNICAL DATA SHEET

Welding Spray

Zetex Europe B.V.

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31 (0)888-93 88 39

info@zetex.com

www.zetex.com

Product description

Zetex Welding Spray is an environmental health friendly spray without silicons. Can be sprayed in all directions and is non-flammable.

Product benefits

- Dissolves and emulsifies all conventional automotive oils and greases.
- Ease of use.
- Fast use. Instantaneous emulsification in water.

Applications

You can use Zetex Welding Spray on any metallic substrate, for the removal of greases, oils, bitumen and tar stains, waxes etc. This product is also suitable for spot removal use on concretes, and on many plastics and painted surfaces subject to successful assessment on an inconspicuous area. Please don't use it on asphalt surfaces.

Shake the Welding Spray before use. Spray liberally on the designated area. Allow to remain in contact with the surface for a few minutes to penetrate and solublise contaminants and rinse off with water. Brushing or other forms of agitation will assist in effective solubilisation of deposits. Always dispose of contaminated materials in a sealable metal bin to prevent fire risk.

Available form

Aerosol 500 ml

Colour

Transparent

Safety recommendations

Please read our MSDS before using this product.

Properties	Specification
Appearance	A colourless liquid with a hydrocarbon odour
pH	Not applicable
Specific gravity	0.785 +/- 0.015
Flammability, as supplied	Extremely flammable, flash point below -20
Composition Data	A solution of coconut diethanolamide and synthetic fragrance in white spirit and xylene, in a butane/isobutane/propane propellant.
Non-Volatiles % m/m	1.00-5.00
Service temperature	Designed for use at ambient temperatures
Active content % m/m, as supplied	70-80
Viscosity	Thin free flowing liquid