



STICK WITH US

## TECHNICAL DATA SHEET

### Easy Silicone Neutral Sanitary



#### Zettex Europe BV

Partridgeweg 1, 4791 RV Klundert

The Netherlands

+31 (0)888-93 88 39

[info@zettex.com](mailto:info@zettex.com)

[www.zettex.com](http://www.zettex.com)

#### Product Description

Zettex Easy Silicone Neutral Sanitary is an oxym based universal sealant with excellent mold and bacteria-resistant properties. Zettex Easy Silicone Neutral Sanitary is colourfast and UV-resistant and therefore the perfect all-round sealant for all types of connection joints in bathrooms, swimming pools, saunas and other high-humidity areas.

#### Material

Alkoxy silicone.

#### Properties

- Permanently elastic.
- Odorless, acid-free.
- High UV and water resistance.
- Durable and colourfast.
- Anti-fungal protection.
- Excellent primerless bonding for a wide range of substrates.
- High range of motion. In accordance with ISO 11600-F&G 25LM standards.
- Excellent measuring properties .

#### Application areas

For sealing all types of joints in sanitary areas, joints between sandwich panels and areas with high moisture content. Can be used as a seal along window frames, as a seal in cold stores, kitchens, swimming pools, polycarbonate patio roofs and almost all types of natural stone. Sealing on porous and non-porous surfaces where mould is present.

#### Utilization

The surface must be clean and free of dust, grease and oil residue. This can be removed using the Zettex Profireiniger. Spray the Profireiniger on a Zettex Bonte or Witte tricot cloth and then remove the residue. The Zettex Easy Silicon Neutral Sanitary adheres to most surfaces without primer. However, a test beforehand is recommended. If you have any doubts about using a primer beforehand, please contact our technical department! Building materials with leaking oil, plasticizers or solvents. No adhesion is possible on PE, PP, PTFE. In addition, Zettex Easy Silicon S cannot be painted over .

#### Packaging

- Tube 310 ml
- Sausage 600 ml
- Sausage 400 ml

#### Colour

White, off white , ral 9001, light grey, sanitary grey, transparent grey, transparent, black, anthracite ral 7016, manhattan , buxy . Other colours are available on request. Request the Easy Silicon S colour chart now without obligation .

**Safety recommendations**

Always read the safety information before use.

**Shelf life**

Shelf life 18 months in unopened packaging. Store at temperatures between 5°C and 25°C.

**Certificates**



Properties	Specifications
Basic	Neutral alkoxy silicones
Specific weight	About 1.02 g/ml
Skin formation time (at 23 °C; 50 % RH)	5-15 min
Degree of hardening	About 3mm/25 hours
Flow resistance (ISO 7390)	0 mm
Loss of volume (ISO 10563)	<5%
Stretch to break	600%
Maximum distortion (ISO 11600)	About 25%
Elastic recovery (ISO 7389)	>85%
Shoare A Hardness (ISO 868)	30
Application Temperature	Between 5 and 40 degrees
Temperature resistance	-40°C to 150°C